



CONSULT FACTORY FOR SPECIAL CONFIGURATIONS.

	POS 1 POS 2 (STD)	UNITS ARE AVAILABLE IN FAIL CLOCKWISE OR FAIL COUNTERCLOCKWISE, UNIT SHOWN IN FULL CCW (OPEN) POSITION FOR FAIL CLOCKWISE; CCW TO COMPRESS SPRING. GREASED FOR LIFE. PLATED STANDARD SHAFT.	MAX DRIVER BORE & KEY		<b>HANDWHEEL</b>  RECOMMENDED Ø: 24 IN RIM PULL AT MAX TORQUE: 82 LBS TURNS FOR 90°: 300	RATIO: 1200:1 TORQUE: 260,000 IN LBS [29376 N-M] TEMPERATURE: -20° TO 150°F [-29° TO 66°C]  WEIGHT UNIT: 525 LBS [238.1 KG] DRIVER: 231 LBS [104.8 KG] HANDWHEEL: 8 LBS [3.6 KG]
			MAX IN LINE Ø 5.000 1.000 X .750 KEY	MAX Ø 5.250 1.500 X 1.000 KEY		

42-63XXA 3/19/07

HOUSING MOUNTING PATTERN				COVER MOUNTING PATTERN				<b>MANUAL 1/4 TURN ACTUATOR          COMMERCIAL GRADE</b>  <b>DYNATORQUE</b> WWW.DYNATORQUE.COM		<b>DT260          SRD</b>
MAX	MAX ON CENTER	STD	MIN	MAX	MAX ON CENTER	STD	MIN			
Ø 15.500 1-8 UNC	Ø 15.500 1-8 UNC	Ø 14.016 1 1/8-7 UNC	Ø 10.000 5/8-11 UNC	Ø 15.000 Ø 1.188	Ø 15.000 Ø 1.188	Ø 14.016 Ø 1.188	Ø 12.450 Ø .688			