



STANDARD 20° TEST POSITION. SHOWN IN HOME POSITION. GREASED FOR LIFE. STANDARD STAINLESS STEEL SHAFT. STANDARD STAINLESS STEEL ENGAGEMENT KEY.	WORM WHEEL GEAR BORE		MAX DRIVE COUPLING BORE & KEY		CONSULT FACTORY FOR SPECIAL CONFIGURATIONS AND SWITCH MOUNTING OPTIONS	TORQUE: 260,000 IN LBS [29385 N-M] TEMPERATURE: -20° TO 150°F [-29° TO 66°C] WEIGHT UNIT: 415 LBS [188.2 KG] DRIVER: 265 LBS [120.2 KG] KEY: .9 LBS [.4 KG]
	MAX W/W BORE	STD W/W BORE	MAX IN LINE COUPLING	MAX COUPLING		
	Ø 7.000 1.250X.625 KEY	Ø 6.250 1.500X1.000 KEY	Ø 5.000 1.000X.750 KEY	Ø 5.250 1.500X1.000 KEY		

HOUSING MOUNTING PATTERN				COVER MOUNTING PATTERN				PARTIAL STROKE TESTING UNIT COMMERCIAL GRADE	
MAX	MAX ON CENTER	STD	MIN	MAX	MAX ON CENTER	STD	MIN	DYNATORQUE WWW.DYNATORQUE.COM	DT260 D-STOP
Ø 15.500 1-8 UNC	Ø 15.500 1-8 UNC	Ø 14.016 1-1/8-7 UNC	Ø 10.000 5/8-11 UNC	Ø 15.000 Ø 1.188	Ø 15.000 Ø 1.188	Ø 14.016 Ø 1.188	Ø 12.750 Ø .688		

50-51XX 5/10/05