



CONSULT FACTORY FOR SPECIAL CONFIGURATIONS

		UNIT SHOWN IN OPEN POSITION. UNITS ARE AVAILABLE IN LOCK CLOSED OR LOCK OPEN, UNIT SHOWN IS LOCK CLOSED. GREASED FOR LIFE.	MAX DRIVER BORE & KEY		3/4" HEX DRIVE FOR INPUT SHAFT		TORQUE: 12,000 IN LBS [13568 N-M] TEMPERATURE: -20° TO 150°F [-29° TO 66°C] WEIGHT UNIT: 32 LBS [14.5 KG] DRIVER: 7 LBS [3.2 KG]				
			MAX IN LINE ϕ 1.250 .250 X .188 KEY	MAX ϕ 1.500 .375 X .250 KEY	PADLOCK: 1/4" SHANK OR SMALLER APPROXIMATE TURNS FOR ENGAGEMENT : 14.25						
HOUSING MOUNTING PATTERN				COVER MOUNTING PATTERN				COMMERCIAL GRADE D-LOCK			
MAX	MAX ON CENTER	STD	MIN	MAX	MAX ON CENTER	STD	MIN	DYNATORQUE WWW.DYNATORQUE.COM 6/28/05			
ϕ 6.496 3/4-10	ϕ 5.250 1/2-13	ϕ 4.921 1/2-13	ϕ 3.750 3/8-16	ϕ 6.496 ϕ .812	ϕ 5.375 ϕ .688	ϕ 4.920 ϕ .562	ϕ 4.750 ϕ .562				