



	LOCK OPEN LOCK CLOSED CCW CW	UNIT SHOWN IN OPEN POSITION. UNITS ARE AVAILABLE IN LOCK CLOSED OR LOCK OPEN, UNIT SHOWN IS LOCK CLOSED. GREASED FOR LIFE.	MAX DRIVER BORE & KEY		3/4" HEX DRIVE FOR INPUT SHAFT PADLOCK: 1/4" SHANK OR SMALLER APPROXIMATE TURNS FOR ENGAGEMENT: 13.25	TORQUE: 63,000 IN LBS [7119 N-M] TEMPERATURE: -20° TO 150°F [-29° TO 66°C] WEIGHT UNIT: 79 LBS [35.9 KG] DRIVER: 28 LBS [12.7 KG]
			MAX IN LINE ϕ 1.875 .500 X .375 KEY	MAX ϕ 2.500 .750 X .500 KEY		

HOUSING MOUNTING PATTERN				COVER MOUNTING PATTERN				COMMERCIAL GRADE ZERO LOCK DYNATORQUE WWW.DYNATORQUE.COM 6/28/05		DT36 D-LOCK
MAX ϕ 9.000 3/4-10	MAX ON CENTER ϕ 7.875 3/4-10	STD ϕ 6.496 3/4-10	MIN ϕ 6.000 5/8-11	MAX ϕ 10.000 ϕ .688	MAX ON CENTER ϕ 7.188 ϕ .812	STD ϕ 6.500 ϕ .781	MIN ϕ 6.000 ϕ .688			